

## VERTICAL SEAM CLOSER



This machine is designed for post-production sealing of square or rectangular cross-section ventilation ducts. It efficiently performs the closing process using the Pittsburgh seam method, resulting in a tighter clamp shape and reduced air permeability. It is compatible with all flange types, operates quickly, and user-friendly.



### Technical Details

Power	:	4,5 KW
Voltage-Frequency	:	380/400V 50Hz 3Ph
Current	:	10,5A
Sheet Thickness	:	0,50mm - 1,20mm
Duct Length	:	1000mm - 1500mm
Duct Flange Size	:	Suitable for All Flange Forms
Machine Dimensions	:	1,1m x 0,9m x 2,1m
Machine Weight	:	1000 Kg
Control Type	:	Automatic + Pedal
Seam Types	:	Pittsburgh
Hydraulic Unit	:	Yes



## CORNERMATIC



This machine is designed to attach the necessary corner apparatus to TDF Self-flanged channels using bolts. The machine automates the corner feeding process through a built-in corner hopper, resulting in swift and secure fastening. This automation eliminates the need for manual intervention by the operator, ensuring a safe working environment.



Technical Details	Hydraulic	Pneumatic
Power	: 4 KW	0,3 KW
Voltage-Frequency	380-400 V / 3PH+PE / 50Hz	220 VAC 50Hz / 1PH+N+PE
Current	: 10A	1,3A
Sheet Thickness	: 0,50mm - 1,2mm Galvanized 0,50mm - 0,80mm Stainless Steel	0,50mm - 1mm Galvanized 0,50mm - 0,60mm Stainless Steel
Air Pressure	: None	6 Bar 196 lt/min
Dimensions	: 1250mm x 800mm x 1050mm	1250mm x 800mm x 1050mm
Machine Weight	: 400 Kg	285 Kg
Options	: L20, L25, L32	L20, L25, L32
Work Type	: Automatic / + Pedal	Automatic / + Pedal